



Load Stabilizer T124 ST





Specification:

The KAUP Telescopic Load Stabilizer T124ST has a large opening range with a low construction height. Therefore this Load Stabilizer is best suited for large volume goods, e.g. for stabilizing and securing stacks of Euro pallets.



Attachment is operated hydraulically, i.e. supplied with oil from the forklift truck's hydraulic system. Truck requires one additional hydraulic function.



Load Stabilizer T124 ST

Technical specifications

Model													
1T124ST	1.515	1.175-2.995	1.650	605	800	1.000	3.700	3	204	217	749	1.732	273
1T124ST	1.515	1.175-2.995	1.650	605	800	1.000	3.700	2	204	217	749	1.732	273
1T124.1ST	1.190	950-2.570	1.550	605	800	1.000	3.700	3	204	231	627	1.515	248
1T124.1ST	1.190	950-2.570	1.550	605	800	1.000	3.700	2	204	231	627	1.515	248
1T124.2ST	940	750-1.930	1.160	605	800	1.000	3.700	3	204	253	522	1.190	216
1T124.2ST	940	750-1.930	1.160	605	800	1.000	3.700	2	204	253	522	1.190	216



Load Stabilizer T124 ST



Qualities:

- Solid construction
- Good visibility conditions
- Combination with other attachments possible



- The total height is the result of adding fig. A + C.
- To choose the right fork length please consider dimension "V".
- The standard contact pad frame is alternatively available in 770 x 920 mm or 800 x 1.000 mm.
- Increased contact pad on request.

Product Images





