


Four Pallet Handler / Eight Pallet Handler T419-2-4 / T419-4-8L

with independent sideshift - for 2 or 4 pallets side by side or 4 or 8 pallets - 2 hydraulic functions



Specification:

The KAUP Four / Eight Pallet Handler type T419-2-4/T419-4-8-L can transport up to eight pallets at the same time and speeds up loading and unloading of trucks, wagons and storage racks considerably. The innovative visibility improved design ensures a good view to the fork tips and load. The practice orientated construction from T-profiles and C-profiles ensures highest stability and long operating hours with extended intervals between servicing and a minimum of required maintenance.



Multi Pallet Handling: For 2 or 4 pallets next to each other or e.g. 4 or 8 pallets in front of and next to each other.



Attachment has separate sideshift as standard. The maximum allowable sideshift stroke (e.g. ± 100 mm) is always available independent of fork or arm position (with clamps or fork positioners).



Attachment is operated hydraulically, i.e. supplied with oil from the forklift truck's hydraulic system. Truck requires two additional hydraulic functions.



Four Pallet Handler / Eight Pallet Handler T419-2-4 / T419-4-8L

Technical specifications

Model														
4T419-4-8L	3.600	1.200	±160	1.365-2.965	1.950	60	70	120	70	2.350	4	194	612	1.655
12T419-4-8L	8.000	1.200	±160	1.365-2.965	2.500	80	70	150	80	2.400	Pin-Type	305	554	3.110
6T419-2-4	4.800	600	±160	1.365-2.965	1.950	45	50	120	70	1.150	4	192	257	1.320
6T419-2-4	4.800	600	±250	1.365-2.965	1.950	45	50	120	70	1.150	4	192	256	1.325



Four Pallet Handler / Eight Pallet Handler T419-2-4 / T419-4-8L



Qualities:

- Four / Eight Pallet Handler for heavy duty tasks
- Good residual capacity
- Good visibility conditions
- Synchronized for quicker working speeds
- Independent sideshift serially



Product Images

