


Rotating Bale Clamp T453/180

Rotation 360° continuous - with additional pair of forks to empty various boxes - 2 hydraulic functions



Specification:

An additional fork pair distinguishes this attachment from the Rotating Bale Clamp T453 and allows easy and safe emptying of the most different transport containers or grid boxing with suitable insertion slots.



Attachment rotates hydraulically by 360° endless in both directions.



Attachment is operated hydraulically, i.e. supplied with oil from the forklift truck's hydraulic system. Truck requires two additional hydraulic functions.



Attachment is serially designed without sideshift. It can be fitted with separate or valveblock sideshift upon request.



Attachment is designed with toe-in on the tips which should be taken into account when choosing the opening range.



Attachment is available with cylinder and sideshifter protection.



Rotating Bale Clamp T453/180

Technical specifications

Model																	
1,5T453/180	1.250	500	655-1.755	970	440	37	1.200	125	6.013	7,6	2B	267	427	153	652	45	1.200
1,5T453/180	1.250	500	655-2.005	1.200	440	37	1.200	125	6.013	7,6	2B	267	420	155	668	45	1.200
2T453/180	2.000	500	575-1.875	1.040	440	42	1.200	150	7.700	9,7	2B	285	411	204	863	50	1.200
2T453/180	2.000	500	585-1.985	1.130	440	42	1.200	150	7.700	9,7	2B	285	409	205	871	50	1.200
2T453/180	2.000	500	585-2.185	1.330	440	42	1.200	150	7.700	9,7	2B	285	405	206	886	50	1.200
2T453/180	2.000	500	575-1.875	1.040	440	42	1.200	150	7.700	9,7	3B	285	411	204	863	50	1.200
2T453/180	2.000	500	585-1.985	1.130	440	42	1.200	150	7.700	9,7	3B	285	409	205	871	50	1.200
2T453/180	2.000	500	585-2.185	1.330	440	42	1.200	150	7.700	9,7	3B	285	405	206	886	50	1.200
3T453/180	2.500	500	695-2.095	1.130	470	47	1.200	150	8.950	11,3	3B	304	409	232	1.084	50	1.200
3T453/180	2.500	500	675-2.175	1.330	470	47	1.200	150	8.950	11,3	3B	304	406	234	1.102	50	1.200



Qualities:

- Good visibility conditions
- Stable construction
- Rotation 360° endlessly
- Optionally with sideshift available



- Attention: Additional forks exclusively possible with underclearance according to ISO class »B« version
- Note: Container must have suitable insertion slots.
- Also available with sideshift, model T493/180 on request

Product Images

